



Powerful Solutions

EagleEyes CCTV

SECURITY SOLUTIONS AND TECHNOLOGIES

Day&Night Zoom Camera 23X

- Superior Sensitivity With DSS (Digital Slow shutter)
- 1/3" Interline transfer SONY Super HAD CCD image sensor
- Driver zoom lens with maximum power of 23X optical zoom 10X digital zoom
- Specially designed for challenging 24 hours surveillance applications
- Excellent picture quality with Super Dynamic Range
- Day& Night mode: Color converts to B&W in low light with DOUBLE ICR (Infrared Cut filter Removal) function and low light at 0.001 Lux (DSS ON)
- Superior sensitivity with DSS(Digital Slow shutter)
- Support camera control RS485 (PelcoD/P protocol, EagleEyes, others), Motion detection, AWB, AGC, PIP, BLC, Mirror, DNR, Freeze, Other functions OSD.
- Incredible S/N ration of 52dB with DNR(Digital Noise Reduction)



Model	EE-Z2360NL
Signal system	PAL or NTSC System 1.0 Vp-p,75 Ohm
Image sensor	1/3" Sony Super-HAD Color CCD
Active pixel	811(H)x508(V)(NTSC) / 795(H)x596(V)(PAL)
Horizontal Resolution	480 TV Lines (Color) / 570TV Lines(B/W)
Min scene illumination	0.1Lux(color),0.01Lux(B/W) / 0.001Lux(Low-shutter mode)
S/N ratio	52dB(AGC OFF)
Focus Length	3.6mm~82.8mm
Iris	F1.2~F32
Zoom Ratio	Digital:10X / Optical:23X
Minimum Object Distance	(X1-X4)10cm,(X5-X22)1m
Exposure control	Auto, Manual, IRIS PRI, Shutter PRI,AGC on/off
Function	Digital zoom, AWB, B/W, Mirror, PIP, Freeze DNR, BLC, Title, Camera ID, Motion detection, etc
Communication	RS485 integrated (Protocol PelcoD/P, EagleEyes, others)
Power Requirement	DC12V ±10%(4.3W)
Dimension	60(W)×67(H)×105(D)mm
Weight	315g approximately
Tolerance Temperature	-10°C to + 55°C RH95%(MAX)
Tolerance Humidity	0%~96%



Av. República Argentina, 50 • 15º andar
 Curitiba PR 80240-210
 Tel: (041) 3342 1600 • Fax: (041) 3244 2200
 vendas@eaglevision.com.br
 www.eaglevision.com.br

