



Powerful Solutions

EagleEyes CCTV

SECURITY SOLUTIONS AND TECHNOLOGIES

Zoom Camera 27X Day&Night

- LG CCD camera chip set DSP
- High resolution at 480 Lines
- 0.5Lux with Day & Night function
- Control by RS485 (receiver required) or manual
- OSD (On screen display)
- 27X Optical zoom (3.5~91.0mm) and 10X Digital zoom



Model	EE-LV2700DN	EE-LV2700DP
Signal System	NTSC : 525 Lines	PAL : 625 lines
Scanning System	2:1 Interlace	
Scanning Frequency(H)	15.734 KHz	15.625 KHz
Scanning Frequency(V)	59.94 Hz	50 Hz
Image Sensor	1/4 Inch LG CCD	
Total Pixels Number	811(H) x 508 (V) 410K	795(H) x 596 (V) 470K
Effective Pixels Number	768(H) x 494 (V) 380K	752(H) x 582 (V) 440K
S/N Ratio	More Than 50dB (AGC Off)	
Resolution	Horizontal : 480 TV Lines	
Video Output Level	1.0 Vp-p (75 Ohms, Composite)	
Lens	27x Optical Zoom (F1.6, f=3.5~91.0mm) Video AF	
Digital Zoom Ratio	10x (Total Zoom Ratio : 270x), 2x ~ 10x Variable	
Zoom Speed(Optical)	4.0 Sec	
Min. Shooting Distance	1 cm (Wide) / 1 meter (Tele)	
Min. Illumination	0.5 Lux (Day&Night On), 0.1 Lux (Night)	
Camera Control	Zoom, focus (Protocol Receiver optional)	
OSD (On Screen Display)	On / Off	
Day&Night(ICR)	Auto/ Day / Night	
OSD	Yes, configuration	
Color / Black&White	On / Off	
Focus Mode	Auto / Manual	
IR LED and CDS Sensor	Optional	
Shutter Speed(8 Steps)	1/60 ~ 1/10,000 Sec.	
Input / Output Connector	Power:2 Pin Terminal / Video Output:BNC	
Supplied Voltage	DC 9V ~ 15V (Recommendation DC 12V±0.5V)	
Power Consumption	Max. 4.2W / 350mA	
Demensions (WxHxD)	50.5 x 61.1 x 92.25 mm	
Weight	Approx. 300g	



Av. República Argentina, 50 • 15° andar
 Curitiba PR 80240-210
 Tel: (041) 3342 1600 • Fax: (041) 3244 2200
 vendas@eaglevision.com.br • www.eaglevision.com.br

