



Powerful Solutions

EagleEyes CCTV

SECURITY SOLUTIONS AND TECHNOLOGIES

4 Ch Active UTP Video/Audio/Data/Power Transceiver

EE-4410R

- 4 Channels Twisted Pair TX Component
- BNC Plug to CAT-5 twisted pair terminal
- ACTIVE Video, Audio, Data & Power Transm/Receiver
- Range UP TO 1500 METERS
- Internal impedance coupling device
- Surge protection built-in
- Control: Class 6 gain, luminance controllable
- Video I/P: 1V p-p 75ohm



Characteristics	It can be integrated with Active Transceiver Series to transmit the color video, audio & data signal up to 1500m, and power up to 200meters.
Distance Control	Amplified Switchers
Image Quality Control	Brightness and Sharpness
Audio	14dB
Channels	4 Video/Audio/Data/Power interfaces
Power Supply	DC 12V
Cable	Cable: Cable 5 or Above (24AWG or Stronger)
Normal Output Level	1Vp-p\75• TV signal
Bandwidth	DC~6MHz
Differential Gain	2%
Differential Phase	2°
Resistance	Unbalanced termination 75Ω Balanced
Surge Protection	6000V 1.2uS x 50uS
Termination	100Ω
Weighted Signal-noise-ratio	60dB
Power consumption	0.5w
Operating Temperature Tange	-25°C~+70°C
Operating Humidity Range	~95%(Non-condensing)
Dimensions	180x70x25mm