




Powerful Solutions

EagleEyes CCTV

SECURITY SOLUTIONS AND TECHNOLOGIES

Vandal-Proof Dome Day&Night Varifocal 540 Lines

- VANDAL-PROOF Dome day/night function with 1/3" SONY CCD.
- VARIFOCAL LENS 3.5-8mm (2.6-6.0mm or 4-9mm optional).
- High-Resolution at 540 lines and low light 0.1lux (Day) / 0.01 (Night)
- Vandal-proof housing and cover water-proof IP66
- Auto Gain Control (AGC) and Back-Light Compensation (BLC)
- Auto White Balance (AWB) 3200~10000K.
- 3D bracket provide adjustment of 3 rotation angle.



Model	EE-D503HVF-VP
Signal System	NTSC : 525 Lines
Scanning System	2:1 Interlace
Scanning Frequency(H)	15.734 KHz
Scanning Frequency(V)	59.94 Hz
Image Sensor	1/3" SONY CCD - DSP
Total/Effective Pixels	768x494 pixels
S/N Ratio	More than 50dB(AGC Off)
Resolution	Horizontal : 540 TV Lines
Video Output Level	1.0 Vp-p (75 Ohms, Composite)
Lens	Varifocal 3.5-8mm (2.6-6.0mm or 4-9mm optional) AI Optional
Sync System	Internal (Line-lock on 24VAC models)
Sensitivity	0.1 lux (Day) ~ 0.01 Lux (Night) ~ 0.0 Lux (IR On)
Electronic Shutter	1/60 ~ 1/120,000 Sec
White Balance	Auto (3200~10000K)
AGC	ON/OFF Dip Switch
BLC	ON/OFF Dip Switch
AES	ON/OFF Dip Switch
Mirror	ON/OFF Dip Switch
Input/Output Connector	BNC / DC jack
Operating Temperature	(-) 10°C ~ (+) 55°C
Supplied Voltage	12VDC (12VDC/24VAC Optional)
Vandal Resistance	Yes, Polycarbonate Cover and Aluminum Base, IP66
Dome Size	120 x 74mm / 3D bracket
Weight	Approx. 225g



Av. República Argentina, 50 • 15º andar
 Curitiba PR 80240-210
 Tel: (041) 3342 1600 • Fax: (041) 3244 2200
 vendas@eaglevision.com.br
 www.eaglevision.com.br



IP66

