



Powerful Solutions

# EagleEyes CCTV

## SECURITY SOLUTIONS AND TECHNOLOGIES

### LCD CCTV Monitor 17" 3D Filter & Deinterlace

- Newest High Performance **Deinterlace Chip** to improve Picture Quality
- **3D Comb Filter** to reduce **Signal Noise**
- NTSC/PAL Auto Detect
- Multi signal inputs supported - VGA (D-Sub), RCA(Composite Video) and **BNC Video-in Connectors**
- Mini-jack Connector Audio-in
- Support VESA 75x75 wall mount kit 1+
- Support up to 1280 x 1024 SXGA High Resolution with Vivid Color
- Video Auto Adjust (VGA mode)
- High Contrast Ratio up to 500:1, 8ms
- 4 watts Stereo Speakers with Amplifier included
- Low Power Consumption (30 watts max; stand-by mode 3 watts)
- 100~240 VAC 60/50 Hz Universal Power Supply
- High Performance and Long Lifetime Design

**EE-LCD17-3D**



Deinterlace with 3D Comb Filter monitor



Other Display



Av. República Argentina, 50 • 15° andar  
Curitiba PR 80240-210  
Tel: (041) 3342 1600 • Fax: (041) 3244 2200  
vendas@eaglevision.com.br • www.eaglevision.com.br





Powerful Solutions

# EagleEyes CCTV

## SECURITY SOLUTIONS AND TECHNOLOGIES

### Technical Specification

|                       |   |
|-----------------------|---|
| <b>Model No.</b>      | <b>EE-LCD17-3D</b>  |
| Size                  | 17 inches   |
| LCD Display           | 337.9(H) x 270.3(V) mm  |
| Viewing Angle H/V     | 140/140(Typ.)   |
| Dot Distance          | 0.264(H) x 0.264(V) m   |
| Light                 | 4 CCFL  |
| Resolution            | 1280 x 1024 (SXGA)  |
| Horizontal Frequency  | 30K-80 kHz  |
| Vertical Frequency    | 56V 75 Hz   |
| Display Color         | 16.7M   |
| Signals               | ANALOG RGB SIGNALS  |
| Signal Input          | 15-PIN D-SUB, AUDIO INPUTx1, BNCx1  |
| Brightness            | 420(cd/m <sup>2</sup> )   |
| Contrast Ratio        | (500:1)   |
| Response Time         | 8ms   |
| Consumption           | 30W(MAX),3W(STAND MODE)   |
| VESA                  | VESA DDC 2B   |
| Panel Control         | 5 KEYPAD, POWER, MENU/ENTER, UP/RIGHTDOWN/LEFT, EXIT                      |
| OSD Control           | AUTO CONFIG, BRIGHTNESS, CONTRAST, COLOR-TEMP, IMAGE QUALITY              |
| Operation Temperature | OPERATION:0~50° STORAGE:-20~60°   |
| Speaker               | 2W x 2 SPEAKER WITH AMPLIFIER   |
| Save Power            | VESA DPMS   |
| Power Input           | 110-240VAC(60/50Hz)   |
| Dimension             | 395(W)x395(H)x170(D)mm  |
| Net Weight(N.W/G.W)   | 5.15Kg / 7.01Kg   |
| Agency Approval       | FCC,CE, Energy star, BSMI   |
| Option Connections    | Mini-jack audio-in, 15pin D-Sub, RCA-Video-in, BNC-video-in, RCA-Audio-in |



Av. República Argentina, 50 • 15° andar  
 Curitiba PR 80240-210  
 Tel: (041) 3342 1600 • Fax: (041) 3244 2200  
 vendas@eaglevision.com.br • www.eaglevision.com.br

