



Powerful Solutions

EagleEyes CCTV

SECURITY SOLUTIONS AND TECHNOLOGIES

16 Output 24VAC 1U 19" Rackmount Power Supply

- Built in PTC (positive temperature coefficient) for short protection and auto rework on each port.
- Transformer with Tension Regulator Integrated
- Built in fuse breaker to avoid current overload
- 110/220VAC Input and 24VAC 8A or 12.5A output
- Input and output surge suppression
- 1 amp output max. per channel
- Maintains camera synchronization
- Standard, 1U EIA 19" rack mount chassis
- Fixed terminal strips for field wiring
- 3 wire grounded AC line cord
- Input and output fuse protected

SPECIFICATIONS

Input Specifications:

- Input voltage: 120/220 VAC (selectable)
- Input voltage frequency: 60 Hz
- Input current: 3.5 A

Output Specifications:

- Output voltage: 24VAC
- Total output current: 8A or 15A
- Outputs: 16, PTC protected
- Power limited @ 1.0A

Temperature Ratings:

- Operating temperature: 0 °C to 49 °C
- Humidity: 85% @ 30 °C
- BTU/hr: 34

EE-PW816R (24VAC 8A)
EE-PW1216R (24VAC 12.5A)



CURRENT INFORMATION:

- Short Cut Time: 0.2 Sec/ Port
- Cut Current / Time: 2.5A/ 4Sec
- Resettable Output: 2.5A/ 4Sec
- Resettable Output Time: 1 Sec (Min)

MECHANICAL

- 1U rack mount chassis: 2.25" H x 19.125" W x 10" D
- 16 gauge galvanized steel

APPLICATIONS

- Digital color cameras
- Monochrome cameras
- Indoor/outdoor fixed domes
- PTZ's
- IP cameras
- Fiber optic senders/receivers