



Powerful Solutions

EagleEyes CCTV

SECURITY SOLUTIONS AND TECHNOLOGIES

Keyboard for DVR, NVR & SpeedDome

- Three-dimension joystick with zoom on joystick
- Blue screen Large LCD display
- Support different Protocols, Baud Rates with RS485 Bus Line.
- Password management parameter setting which is safe, reliable, preventing change the parameter setting by mistake.
- The speed of the PTZ dome can be controlled by the scope of the joystick swing which can be showed on the LCD screen.
- Online refreshed new program protocol, the protocol customer need, the updated firmware program via RS485 communication connection.
- Built in multi-protocols protocol.
- Network ethernet connexion using UTP port
- Control 256 units of PTZ, Domes & decoder with address code 0-255.
- Can connect with 16 subsidiary controllers, controller ID is 0-15.
- Control of DVRs, NVRs EagleVision and Speeddome
- 256 Presets configurations
- Photoelectricity separate RS485 Signal Input/Output up to 1200m.

EE-KB1001 Series



TECHNICAL SPECIFICATION

MODELS: EE-KB1010N (3 axis/Network) / EE-KB1010N (3 axis / Standard)	
Communication	MASTER : RS485 (2400bps, 4800bps, 9600bps) SLAVE : RS232 (2400bps, 4800bps, 9600bps) LAN : (EE-KB1001N)
Joystick	3-Axis (Joystick Zoom IN/OUT)
Power Consumption	12VDC, 110mA
Display Type	2 LCD Display: 1 with 20 x 4 Character and 1 with 20 x 7, With Blue Backlight
Key Type	PC Key board Button
Keyboard Connector Type	1 RJ45 UTP (Network), 1 RJ45 (RS232), 1 RS485, 4 alarm output
Junction Box Connector	Master : Terminal Block. Slave : 9 Pin D-SUB Connector, 8 Pin Modular
Humidity	10% ~ 70% non Condensing
Controls	Up to 32 DVRs/NVRs EagleVision and 256 Speeddomes
Web	Control IP Cameras and Web Servers
Firmware Upgrade	RJ45 Internal programing
Dimension	140(W) x 185(H) x 365(D)
Weight	1.2kg



Av. República Argentina, 50 • 15º andar
 Curitiba PR 80240-210
 Tel: (041) 3342 1600 • Fax: (041) 3244 2200
 vendas@eaglevision.com.br
 www.eaglevision.com.br

