



Powerful Solutions

# EagleEyes CCTV

## SECURITY SOLUTIONS AND TECHNOLOGIES

### Keyboard for SpeedDome & DVR/NVR

EE-KBD53

- Three-dimension joystick, 160X32 Blueness screen LCD display.
- Support different Protocols, Baud Rates with RS485 Bus Line.
- Support Joystick zoom (3D) to control zoom in/out
- Password management parameter setting which is safe, reliable, preventing change the parameter setting by mistake.
- The speed of the PTZ dome can be controlled by the scope of the joystick swing which can be showed on the LCD screen.
- Support DVR and NVR control for EaglePlus Series
- Online refreshed new program protocol, the protocol customer need, the updated firmware program via RS485 and USB.
- Matched with 12 kinds of PTZ Dome, decoder protocol.
- Can control 255 sets PTZ Domes, decoder with address code 0-254.
- Can connect with 16 subsidiary controllers, controller ID is 0-15.
- Photoelectricity separate RS485 Signal Input/Output up to 1200m.



### TECHNICAL SPECIFICATION EE-KBD53

Baud Rate	2400, 4800, 9600, 19200, 38400, 57600 and 112500 Bps
Camera	Speed Dome Camera all function, OSD Camera all function, Zoom lens Camera all function
DVR	Selection Display, OSD Menu, Configuration, Playback, etc
Dimensions	400 (L) × 265 (W) × 165 (H)
Weight	3.0Kg
Humidity	10%~90% RH, Non-condensation
Input Voltage	12VDC (-15/+50%) Power Supply 90~240VAC
Power	DC jack
Power Consumption	5W
RS-485	Terminal block, RJ-11
USB	1 port integrated
Safety Approval	CE, FCC
Signal	RS-485 (multi-port half-duplex)
Storage Temperature	-10°C~60°C
Transmitting Distance	1200m Max
	Built-in multi-protocol conversion, compatible with protocol: PELCO-D, PELCO-P, UNIVISION (V1, V2), VICON, VCL, MOLYNX, DIAMOND, GE/KALATEL, BOSH/PHILIPS, AD/SENSORNET, EAGLE EYES, ETC
Video Multiplexer	All function



Av. República Argentina, 50 • 15º andar  
 Curitiba PR 80240-210  
 Tel: (041) 3342 1600 • Fax: (041) 3244 2200  
 vendas@eaglevision.com.br  
 www.eaglevision.com.br

