



Powerful Solutions

EagleEyes CCTV

SECURITY SOLUTIONS AND TECHNOLOGIES

PTZ Decoder with protocols built-in

- Water-proof packing, can be used both indoor and outdoor
- 1 channel input, 3 channel outputs
- Independent working channels
- Real-time data transmission.
- Every channel output provides powerful RS485 driving ability

EE-SAD01



The Protocol decoder-converter is mainly used to solve the unmatched communication protocols problem between controlling device and the device being controlled.

It can transform one protocol to another to realize communication between the devices, Through setting the DIP Switches, it can transform EagleEyes protocol into PELCO-D, PELCO-P, SAMSUNG or KALATEL protocol.

The baud rate of the transformed data is available with 9600bps, 4800bps, 2400bps and 1200bps through setting the DIP Switches. In addition, it has 3 channel RS-485 output with powerful driving ability.

Bit 5	Bit 4	Bit 3	Protocol
OFF	OFF	OFF	Pelco-D
OFF	OFF	ON	Pelco-P
OFF	ON	OFF	Samsun g
OFF	ON	ON	Kalatel



Av. República Argentina, 50 • 15º andar
 Curitiba PR 80240-210
 Tel: (041) 3342 1600 • Fax: (041) 3244 2200
 vendas@eaglevision.com.br • www.eaglevision.com.br